

www.purepro.net

# PRESSURE GAUGES

## PUREPRO PRESSURE GAUGES

- Lower and Center Back Mount
- Brass, 304SS and 316 SS Casings
- Brass or Stainless Steel Internals
- 1.5", 2.5" and 4" Dials
- Dry or Liquid Filled



MEMBER  
Water Quality  
ASSOCIATION

## PUREPRO PRESSURE GAUGES

The minimum operating pressure for a RO unit is 50 psi (pounds per square inch). This unit build-in pressure gauge to monitor the operating pressure of the system. If the operating pressure is too low, an RO pressure boosting pump can be added to increase the operating pressure to the ideal range.

### MATERIALS OF CONSTRUCTION

- CASINGS BRASS, 304 SS AND 316 SS
- INTERNALS BRASS AND 316 SS
- STEMS CHROME PLATED BRASS, 304 SS OR 316 SS
- FACE WHITE ALUMINUM, BLACK AND BLUE PRINT
- LENS CLEAR ACRYLIC
- POINTER ALUMINUM, BLACK
- FLUID UV RESISTANT SYNTHETIC SILICONE
- TEMP RATING 0°F (-18°C) TO 140°F (60°C)

# PRESSURE GAUGES

© PUREPRO USA CORP., ILLINOIS, U.S.A.